

iTcPower


empower your business



Diesel Inverter Generators

Silent, Electric Start

DG1400SEi-T/DG1600SEi-T DG2000SEi-T



www.itcpowergenerator.com

GENERATOR	DG14000SEi-T	DG16000SEi-T	DG20000SEi-T
Frequency (Hz)	50	50	50
Rated Power	10kW/12.5kVA	12kW/15kVA	14kW/18kVA
Max. Power	11kW/13.8kVA	13kW/16.3kVA	15kW/20kVA
Voltage (V)	230/400	230/400	230/400
Current (A)	43/18	52/21.6	60.8/26
Plugs	63A & 32A	63A & 32A	63A & 32A
Display	LED6	LED6	LED6
Fuel tank capacity (L)	46	46	46
Running time @75% load (H)	14.6	12.7	10.8
Sound level @ 7m (dBA)	-	-	-
Battery (V/Ah)	12V 6Ah/45Ah	12V 6Ah/45Ah	12V 6Ah/45Ah
ENGINE	2V88	2V92	2V95
Engine type	Diesel	Diesel	Diesel
Power (hp)	-	-	-
Start	Electric	Electric	Electric
Displacement (CC)	912	997	1247
Oil Capacity (L)	2.8	3.5	3.5
ALTERNATOR	AL-10	AL-12	AL-16
Power (Kw)	10	12	16
Power Factor	0.8	0.8	0.8
Voltage Regulation	PMG	PMG	PMG
DIMENSIONS & WEIGHT			
Net Weight (Kg)	260	290	300
Gross Weight (Kg)	280	310	320
Machine size (mm)	1050*660*880	1050*660*880	1050*660*880
Dimensions Package (mm)	1090*700*1150	1090*700*1150	1090*700*1150

Specifications are subject to continuous product development

Options



30Ah
Battery



36Ah
Battery



4Ah / 6Ah
Lithium Battery



Temperature
Sensor to stop




LED6
Voltage AC
Power output
Frequency / Current
Battery voltage
Working time



ATS/AUTO
module



NSK
bearing



EURO5
catalyst



Preheater



Standard packing

Accessories

ATS BOX



Remote controller

300m

