

# **ITC Power**

empower your business



## **Diesel Inverter Generators**

Silent, Twin-cylinder

### **DGP14100SEi-T**

### **DGP16100SEi-T/DGP21000SEi-T**

### **DGP22100SEi-T/DGP25100SEi-T**



GENERATOR	DGP14100SEi-T	DGP16100SEi-T	DGP21000SEi-T
Frequency (Hz)	50/60	50/60	50/60
Rated Power	10kW/12.5kVA	12kW/15kVA	14kW/18kVA
Max. Power	11kW/13.8kVA	13kW/16.3kVA	15kW/20kVA
Voltage (V)	230/400	230/400	230/400
Current (A)	43/18	52/21.6	60.8/26
Plugs	63A&32A	63A&32A	63A&32A
Display	LED6	LED6	LED6
Fuel tank capacity (L)	46	46	46
Running time @75% load (H)	14.6	12.7	10.8
Sound level @ 7m (dBA)	-	-	-
Battery (V/Ah)	12V 6Ah/45Ah	12V 6Ah/45Ah	12V 6Ah/45Ah
ENGINE	2V88	2V92	2V95
Engine type	Diesel	Diesel	Diesel
Power (hp)	18.7	21.4	25.2
Start	Electric	Electric	Electric
Displacement (CC)	912	997	1247
Oil Capacity (L)	2.8	3.5	3.5
ALTERNATOR	AL10-T	AL12-T	AL16-T
Power (Kw)	10	12	16
Power Factor	0.8	0.8	0.8
Voltage Regulation	PMG	PMG	PMG
DIMENSIONS & WEIGHT			
Net Weight (Kg)	260	290	300
Gross Weight (Kg)	280	310	320
Machine size (mm)	1030*680*880	1030*680*880	1030*680*880
Dimensions Package (mm)	1070*730*1150	1070*730*1150	1070*730*1150
FCL 20'/40'HQ	32/68	32/68	32/68

Specifications are subject to continuous product development

GENERATOR	DGP22100SEi-T	DGP25100SEi-T
Frequency (Hz)	50/60	50/60
Rated Power	16kW/20kVA	18kW/22.5kVA
Max. Power	16.5kW/20.6kVA	18.5kW/23.1kVA
Voltage (V)	230/400	230/400
Current (A)	69.5/28.8	78.2/32.4
Plugs	63A&32A	63A&32A
Display	LED6	LED6
Fuel tank capacity (L)	46	46
Running time @75% load (H)	9.6	8.6
Sound level @ 7m (dBA)	-	-
Battery (V/Ah)	12V 6Ah/45Ah	12V 6Ah/45Ah
ENGINE	2V100	2V105
Engine type	Diesel	Diesel
Power (hp)	27.9	30.5
Start	Electric	Electric
Displacement (CC)	1382	1523
Oil Capacity (L)	3.5	3.5
ALTERNATOR	AL17-T	AL19-T
Power (Kw)	17	19
Power Factor	0.8	0.8
Voltage Regulation	PMG	PMG
DIMENSIONS & WEIGHT		
Net Weight (Kg)	305	305
Gross Weight (Kg)	325	325
Machine size (mm)	1050*660*900	1050*660*900
Dimensions Package (mm)	1090*700*1170	1090*700*1170
FCL 20'/40'HQ	32/68	32/68

Specifications are subject to continuous product development

# Options



30Ah  
Battery



36Ah  
Battery



4Ah  
Lithium Battery



Temperature  
Sensor to stop




LED6  
Voltage AC  
Power output  
Frequency / Current  
Battery voltage  
Working time



ATS/AUTO  
module



NSK  
bearing



EURO5  
catalyst



Preheater



Standard packing

# Accessories

ATS BOX



15M  
cable



Remote controller

300m

